

IN THE CLAIMS

Please cancel claim 1. Claims 2-21 were canceled in an earlier Preliminary Amendment. Please enter new claims 22-35 as follows:

1-21. (Canceled)

22. (New) A track for a railborne vehicle with a long-stator linear drive, said track comprising:

at least one long stator having a plurality of track elements arranged in a line, each of said track elements further comprising

a carrier and at least one functional part arranged on said carrier, said functional part comprising a stator carrier;

at least one stator section received by said stator carrier, said stator section comprising a plurality of linearly aligned stator packets, with each said stator packet having a front end and a back end;

said front and back ends of said stator packets having complimentary respective contour and counter-contour cross-sectional profiles such that said front end of a first stator packet aligns with and overlaps said back end of an adjacent said stator packet in the longitudinal and transverse direction so that a vertically and horizontally acting cogging is established between said adjacent front and back ends.

23. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets are fitted together by being shifted along a longitudinal axis of said stator packets.

24. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets each comprise at least two level, oblique surfaces.

25. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets have corresponding recesses and elevations with flanks aligned in a crossing manner in a cross-sectional plane of said stator packets so as to define said vertically and horizontally acting cogging.

26. (New) The track as in claim 25, wherein said corresponding recesses and elevations define a chess board configuration.

27. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets have corresponding flanks that define a locking engagement between said stator packets in the longitudinal direction.

28. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets are brought into engagement by rotation about a vertical axis of said stator packets.

29. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets engage against each other when said stator packets are rotated along a vertical axis, transverse axis, and longitudinal axis.

30. (New) The track as in claim 22, further comprising a material gap between adjacent said stator packets within a said stator section with a width that is different than a width between adjacent said stator packets of different said stator sections.

31. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets within a said stator section have a different spatial configuration as compared to adjacent said stator packets of different said stator sections.

32. (New) The track as in claim 22, wherein said contour and counter-contour profiles of said front and back ends of adjacent said stator packets have a sufficient overlap to compensate for parallel said long stators in a curved track having a same standard length.

33. (New) The track as in claim 22, wherein said vertically acting cogging between contour and counter-contour profiles of said front and back ends of adjacent said stator packets has a clearance such that upon a suspension failure of a stator packet, said stator packet is supported by but visibly drops relative to adjacent said stator packets.

34. (New) A carrier for a track for a railborne vehicle with a long-stator linear drive, the track having at least one long stator having a plurality of track elements arranged in a line, said carrier comprising:

- a stator carrier;

- at least one stator section received by said stator carrier, said stator section comprising a plurality of linearly aligned stator packets, with each said stator packet having a front end and a back end; and

said front and back ends of said stator packets having complimentary respective contour and counter-contour cross-sectional profiles such that said front end of a first stator packet aligns with and overlaps said back end of an adjacent said stator packet in the longitudinal and transverse direction so that a vertically and horizontally acting cogging is established between said adjacent front and back ends.

35. (New) A stator packet for attachment to a stator carrier for a track for a railborne vehicle with a long-stator linear drive, the track having at least one long stator having a plurality of track elements arranged in a line, including a carrier with an attached stator carrier, said stator packet having a front end and a back end; and said front and back ends having complimentary respective contour and counter-contour cross-sectional profiles such that said front end of a first stator packet aligns with and overlaps said back end of an adjacent said stator packet in the longitudinal and transverse direction so that a vertically and horizontally acting cogging is established between said adjacent front and back ends of aligned stator packets.